

TYGON® ND Series

ACCUFLOW
systems
www.accuflow.com 240-457-4413

The Next Generation
of Non-DEHP Tubing
for the Medical Device Market




SAINT-GOBAIN
PERFORMANCE PLASTICS

Saint-Gobain Performance Plastics, a world leader in the development of higher performance polymer products, offers a new alternative to DEHP-plasticized PVC.

Medical Grade Vinyl Tubing Products

From blood and IV bags to enteral feeding, ECMO and dialysis tubing, polyvinyl chloride (PVC) is widely used throughout the healthcare industry. However, ongoing studies of di (2-ethylhexyl) ester (DEHP), a phthalate plasticizer commonly used in flexible PVC products, have raised concerns regarding its use in medical applications. In response to these changing needs, the Saint-Gobain R&D team has formulated a complete range of non-DEHP plasticized materials that meet DEHP performance criteria for critical attributes including clarity, flexibility, chemical resistance, bondability and shelf life.

Biocompatibility

TYGON® ND Series tubing products were developed specifically for use in medical applications. All formulations are USP Class VI approved. Additionally, the ND 100-65 material carries a full complement of biocompatibility testing, including pyrogenics, hemolytics and toxicity.

Non-DEHP and REACH Compliance

Based upon a unique chemistry developed by Saint-Gobain, TYGON® ND Series tubing was formulated to be Registration, Evaluation, Authorization and restriction of CHemical (REACH) compliant for DEHP. To ensure compliance, every individual compound lot is tested to ensure DEHP levels are <1000 ppm. During the extrusion process, individual product dimensions are maintained and monitored through in-line micrometers and off-line verification with computerized imaging equipment.

Typical Applications

- Dialysis equipment
- Minimally invasive devices
- Peristaltic pumps
- Inhalation equipment
- Medical laboratories
- Blood and IV solutions

TYGON® ND 100 Series Plasticizer: TOTM

Shelf Life: 3 years

Product	Durometer Hardness, Shore A, 15 sec	Color	Tensile Strength, psi (MPa)	Ultimate Elongation, %	Tear Resistance lb f/in (kN/m)	Specific Gravity	Water Absorption, % 24 hrs. @23°C	Compression Set Constant Deflection, % @ 158°F (70°C) for 22 hours
ASTM Method	D2240	–	D412	D412	D1004	D792	D570	D395
ND 100-40	40	Clear	1225 (8.4)	380	70 (12.3)	1.13	0.17	53
ND 100-55	55	Clear	1725 (11.9)	425	145 (25.4)	1.18	0.14	57
ND 100-65	65	Clear	2075 (14.3)	415	185 (32.4)	1.19	0.12	60
ND 100-70	70	Clear	2300 (15.90)	415	210 (36.8)	1.19	0.12	60
ND 100-80	80	Clear	2625 (18.1)	350	275 (48.2)	1.21	0.12	59

ND 100-40 replaces Tygon® S-40-HL / ND 100-65 replaces Tygon® S-50-HL / ND 100-80 replaces Tygon® S-54-HL

TYGON® ND 200 Series Plasticizer: DINCH

Shelf Life: 3 years

Product	Durometer Hardness, Shore A, 15 sec	Color	Tensile Strength, psi (MPa)	Ultimate Elongation, %	Tear Resistance lb f/in (kN/m)	Specific Gravity	Water Absorption, % 24 hrs. @23°C	Compression Set Constant Deflection, % @ 158°F (70°C) for 22 hours
ASTM Method	D2240	–	D412	D412	D1004	D792	D570	D395
ND 200-40	40	Clear	1125 (7.8)	370	60 (10.5)	1.09	0.20	49
ND 200-55	55	Clear	1625 (11.2)	385	120 (21.0)	1.14	0.16	52
ND 200-65	65	Clear	2000 (13.8)	385	155 (27.1)	1.17	0.15	57

TYGON® ND 300 Series Plasticizer: DOA

Shelf Life: 1 year

Product	Durometer Hardness, Shore A, 15 sec	Color	Tensile Strength, psi (MPa)	Ultimate Elongation, %	Tear Resistance lb f/in (kN/m)	Specific Gravity	Water Absorption, % 24 hrs. @23°C	Compression Set Constant Deflection, % @ 158°F (70°C) for 22 hours
ASTM Method	D2240	–	D412	D412	D1004	D792	D570	D395
ND 300-40	40	Clear	1075 (7.4)	435	55 (9.6)	1.10	0.29	55
ND 300-55	55	Clear	1575 (10.9)	435	100 (17.5)	1.14	0.24	60
ND 300-65	65	Clear	1900 (13.1)	415	155 (27.1)	1.16	0.24	59

Shore A Hardness was measured on 1/4 in. buttons
 Unless otherwise noted, all tests were conducted at room temperature (73°F). Values shown were determined on 0.075" thick molded ASTM plaques or molded ASTM durometer buttons.

Global Presence, Local Resource

Saint-Gobain Performance Plastics is the world's leading producer of engineered, high-performance polymer products. Our core competency lies in our process technologies — technologies that transform difficult-to-process materials into useful products for industry. These materials include fluoropolymers (PTFE, PFA and FEP), silicone rubber and a range of other high-performance engineered polymers. Our tradition of excellence goes back more than 300 years through our parent company, Compagnie de Saint-Gobain, one of the world's top 100 industrial corporations, with operations in more than 60 countries. We leverage our global technology to provide worldwide advanced materials research, polymer processing and manufacturing support unmatched by any competitor.



Saint-Gobain Performance Plastics — Portage
2316 W. Wisconsin Street
Portage, WI 53901
Tel: (800) 236-7600
Tel: (608) 742-8541
Fax: (608) 742-4731

Saint-Gobain Performance Plastics — Akron
2664 Gilchrist Road
Akron, OH 44305
Tel: (800) 798-1554
Tel: (330) 798-9240
Fax: (330) 798-6968

Saint-Gobain Performance Plastics — Beaverton
3910 Terry-Diane Street
Beaverton, MI 48612
Tel: (888) 387-0067
Tel: (989) 435-9533
Fax: (989) 435-2355

Saint-Gobain Performance Plastics — Clearwater
4451 110th Avenue North
Clearwater, FL 33762
Tel: (800) 541-6880
Fax: (727) 530-5603

Saint-Gobain Performance Plastics — Taunton
700 Warner Blvd.
Taunton, MA 02780
Tel: (800) 722-7106
Tel: (508) 823-7701
Fax: (508) 823-1438

Saint-Gobain Performance Plastics — Charny
La Mothe-aux-Aulnaies
F-89120 Charny, France
Tel: (33) 3-86-63-78-78
Fax: (33) 3-86-63-77-77

Saint-Gobain Performance Plastics — Neuss
Borsigstrasse 13-15
D-41469
Tel.: +49 (0) 2137-91789-11
Fax: +49 (0) 2137-12667

Saint-Gobain Performance Plastics — Bangalore
Grindwell Norton Ltd,
Devanahalli Road,
Off Old Madras Road,
Bangalore, 560049, India
Tel: +91 80 28472900
Fax: +91 80 280472616

Saint-Gobain Performance Plastics — Lyon
Zone Industrielle de Chesnes - B.P 712
F-38297 Saint-Quentin
Fallavier Cedex, France
Tel: (33) 474 948 222
Fax: (33) 474 942 341

Saint-Gobain Performance Plastics — Suwa
10801-5, Haramura, Suwa-gun
Nagano 391-0106 Japan
Tel: (81) 266-79-6400
Fax: (81) 266-70-1001

Saint-Gobain Performance Plastics — Shanghai
1468 Kun Yang Road, Minhang
Economic & Technological
Development Zone
Shanghai, China 200245
Tel: (86) 21 5472 1568
Fax: (86) 21 5472 2378/5472 2379



TYGON® tubing is not intended for use as an implant material.

Saint-Gobain Non-DEHP tubing contains DEHP levels of <1000 ppm.

TYGON® is a registered trademark.

IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain Performance Plastics tubing for all intended uses. Laboratory and clinical tests must be conducted in accordance with applicable regulatory requirements in order to determine the safety and effectiveness for use of tubing in any particular application.

For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product to be free from defects in materials and workmanship. Our only obligation will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risk, if any, including the risk of injury, loss or damage, direct or consequential, arising out of the use, misuse, or inability to use, this product. THIS WARRANTY IS IN LIEU OF THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED. No deviation is authorized.

Saint-Gobain Performance Plastics Corporation assumes no obligations or liability for any advice furnished by it, or for results obtained with respect to those products. All such advice is given and accepted at the buyer's risk.



www.Medical.Saint-Gobain.com